

Video Compression	H.264
Analog and HD-TVI Video Input	32ch BNC (1.0 Vp-p, 75), PAL / NTSC self-adaptive
Audio Compression	G.711u
Audio Input	4-ch, RCA (2.0 Vp-p, 1 k)
Audio Input Interface	4 Audio in
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 k)
VGA Output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
HDMI Output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Recording Resolution	Main stream: 1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF
Frame Rate	Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA ; Main stream: 1/16 fps ~ Real time frame rate ; Sub-stream: 1/16 fps ~ Real time frame rate
Video Bit Rate	32 Kbps-4 Mbps
Stream Type	Video, Video & Audio
Audio Output	1-ch, RCA (Linear, 1 k)
Audio Bit Rate	64 Kbps
Dual Stream	Support
Playback Resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Synchronous Playback	32ch
Interface Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface
Capacity	Up to 4TB capacity for each disk
Network Interface	1:10M / 100M /1000M self-adaptive Ethernet interface
USB Interface	3 × USB2.0
Serial Interface	RS-232, RS-485, Keyboard
Power Supply	100 ~ 240VAC, 47 ~ 63HZ
Consumption	65W
Working Temperature	-10 °C ~ +55 °C (14°F - 131°F)
Working Humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions	445 × 390 × 70 mm (17.5 × 15.3 × 2.7 inch)
Weight	5Kg (11.0lb)