

Image Sensor	1/3" Progressive Scan CMOS
Signal System	N/A
Effective Pixels	1920(H)*1080(V)
Max. Image Resolution	2.0MP
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	2.8-12mm
Lens Mount	φ14
Adjustment Range	N/A
Day & Night	120dB
Wide Dynamic Range	True WDR
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
Synchronization	Internal Synchronization
Video Output	1Vp-p Composite Output (75Ω/BNC)
S/N Ratio	More than 52dB
Up the Coax	Support
Camera ID	On/off (15 characters, position programmable)
D/N Mode	Color/BW/SMART IR
Auto White Balance	ATW/ AWC-SET/ Indoor/ Outdoor/ Manual
Private Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	On/Off
AGC	Support
Anti-Flicker	On/ Off
Language	English/ Japanese/ CHN1/ CHN2/ Korean/ German/ French/ Italian/ Spanish/ Polish/ Russian/ Portuguese/ Dutch/ Turkish/ Hebrew/ Arabic
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Operating Conditions	-20 °C - 60 °C (-4 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10% (-A series support 24 V AC ± 10%, 12 V DC ± 10%)
Power Consumption	12 VDC: Max. 7W 24 VAC: Max. 10W
Weather Proof	IP66
IR Range	Up to 50m
Dimension	300.82×100.76×107.55mm(11.84"×3.97"×4. 23")

Weight	700 g (1.54 lbs)
---------------	------------------