

<b>Image Sensor</b>	1/3" Progressive Scan CMOS
<b>Signal System</b>	PAL/NTSC
<b>Effective Pixels</b>	1920(H) * 1080(V)
<b>Max. Image Resolution</b>	2.0MP
<b>Min. Illumination</b>	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
<b>Shutter Time</b>	1/25(1/30)s to 1/50,000s
<b>Lens</b>	3.6mm
<b>Lens Mount</b>	M12
<b>Adjustment Range</b>	Pan: 0-360 ; Tilt:0-90, Rotation: 0 - 360
<b>Day &amp; Night</b>	IR Cut filter with auto switch
<b>Wide Dynamic Range</b>	No
<b>Synchronization</b>	Internal synchronization
<b>Video Frame Rate</b>	1080p@25fps/1080p@30fps
<b>HD Video Output</b>	1 Analog HD output
<b>Video Output</b>	No
<b>S/N Ratio</b>	More than 52dB
<b>Scene</b>	Indoor, Outdoor, Indoor1, LOW-LIGHT
<b>Camera ID</b>	On/off (15 characters, position programmable)
<b>AGC</b>	Support
<b>D/N Mode</b>	Color/BW/EXT
<b>Auto White Balance</b>	ATW, AWC-SET, Indoor, Outdoor, Manual
<b>Private Mask</b>	On/Off, maximum 8 zones
<b>Motion Detection</b>	On/Off, maximum 4 zones
<b>BLC</b>	On/Off
<b>Anti-Flicker</b>	On/off
<b>Language</b>	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
<b>Function</b>	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
<b>Operating Conditions</b>	-20 °C - 60 °C (-4 °F - 140 °F) Humidity 90% or less (non-condensing)
<b>Power Supply</b>	12 VDC ; -A: 12 VDC
<b>Power Consumption</b>	Max. 5W
<b>Weather Proof</b>	IP66
<b>IR Range</b>	Up to 100ft
<b>Dimension</b>	114.6 x 89.1mm (4.5" x 3.5")
<b>Weight</b>	300g
<b>Communication</b>	N/A