

Video Compression	H.265+/H.265/H.264+/H.264
Analog Video Input	16-ch, BNC interface (1.0 Vp-p, 75), supporting coaxitron connection
HDTVI Input	5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
AHD Input	1080p25, 1080p30, 720p25, 720p30
HDCVI Input	1080p25, 1080p30, 720p25, 720p30
CVBS Input	PAL/NTSC
IP Video Input	2-chUp to 6 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras
Audio Compression	G.711u
Audio Input	4-ch, RCA (2.0 Vp-p, 1 K)
CVBS Output	1-ch, BNC (1.0 Vp-p, 75), resolution: PAL: 704 × 576, NTSC: 704 × 480
HDMI/VGA Output	VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K(2560 × 1440)/60Hz, 1920 × 1080/60Hz,1280 × 1024/60Hz, 1280 × 720/60Hz, 1024× 768/60H
Encoding Resolution	5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF
Frame Rate	Main stream: 5 MP@12fps/4 MP@15fps/3 MP@18fps 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)
Video Bit Rate	32 Kbps to 10 Mbps
Audio Output	1-ch, RCA (Linear, 1 K)
Audio Bit Rate	64 Kbps
Dual Stream	Support
Stream Type	Video, Video & Audio
Synchronous Playback	8-ch
Remote Connections	128
Network Protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
SATA	2 SATA interface
Capacity	Up to 8 TB capacity for each disk
Two-way Audio Input	1-ch, RCA (2.0 Vp-p, 1 K) (using the 1ST audio input)
Network Interface	1, RJ45 10M/100M self-adaptive Ethernet interface
USB Interface	Front panel: 1 × USB 2.0 / Rear panel: 1 × USB 3.0
Serial Interface	RS-485 (half-duplex)
Alarm in/out	16-Apr

Power Supply	12 VDC
Consumption (without HDD)	≤ 25 W
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working Humidity	10% to 90%
Dimensions (W × D × H)	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)
Weight (without HDD)	2 kg (4.4 lb)