

Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	Motorized VF lens; 2.8 - 12 mm Angel of view: 35.1°-114.5°
Lens Mount	φ14
Adjustment Range	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day&Night	IR cut filter with auto switch
Wide Dynamic Range	No
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
Synchronization	Internal Synchronization
S/N Ratio	More than 62 dB
Up the Coax	Support
Auto White Balance	Auto/MWB
BLC	Support
AGC	Support
Anti-flicker	No
Language	English/Chinese
Function	Wide Dynamic Range; Digital Noise reduction; Mirror; SMART IR
Operating Conditions	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15% -A: 12 VDC±15%, 24 VAC±15%
Power Consumption	Max. 6W -A: Max. 9W
Impact Protection	No
Weather Proof	IP66
IR Range	Up to 40m
Dimension	92mm×84.8mm×269.6mm (3.62"×3.34"×3.34")
Weight	Approx. 900g (1.98lb)