

<b>IP video input</b>	128-ch
<b>Two-way audio</b>	1-ch, RCA(2.0 Vp-p,1kΩ)
<b>Incoming bandwidth</b>	400Mbps
<b>Outgoing bandwidth</b>	400Mbps
<b>Remote connection</b>	256
<b>Recording resolution</b>	8MP/ 5MP/ 3MP/ 1080p/ UXGA/ 720p/ VGA/ 4CIF/ DCIF/ 2CIF/ CIF/ QCIF
<b>LCD Output(Optional)</b>	7" LCD touch screen
<b>HDMI output resolution</b>	HDMI 1 Support 64-Windows Division, HDMI 2 Supports 16-Windows Division, HDMI 3-14; For Built-in Video Wall controller
<b>VGA output resolution</b>	1-ch resolution: 1920 x 1080p/60Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
<b>Audio output</b>	1-ch, RCA(2.0Vp-p, 1KΩ)
<b>Live view/Playback resolution</b>	8MP/ 5MP/ 3MP/ 1080p/ UXGA/ 720p/ VGA/ 4CIF/ DCIF/ 2CIF/ CIF/ QCIF
<b>Capability</b>	44-ch@1080p
<b>SATA</b>	16 SATA interface for 16HDDs
<b>eSATA(optional)</b>	No
<b>Mini SAS</b>	1 mini SAS interface
<b>Capacity</b>	Up to 6TB capacity for each HDD
<b>Array Type</b>	RAID0, RAID1, RAID5, RAID10
<b>Optic Fiber Interface</b>	4 1000 Mbps optic fiber interfaces
<b>Network interface</b>	4 RJ - 45 10/ 100/ 1000 Mbps self-adaptive Ethernet interfaces
<b>Serial interface</b>	RS-232; RS-485(reserved); Keyboard;
<b>USB interface</b>	Front panel: 2 X USB 2.0; Rear panel: 1 x USB 3.0
<b>Alarm in/out</b>	16-Aug
<b>Power Supply Cosnsumption</b>	<=100W
<b>Working Temperature</b>	-10° t0 +55°C(14° to 131°F)
<b>Working humidity</b>	10 to 90%
<b>Chassis</b>	19-inch rack-mounted 3U chassis
<b>Dimensions(W x D xH)</b>	442 x 494 x 146 mm
<b>Weight(without hard disk)</b>	<=15.86kg (31.79)(without hard disk)