

Image Sensor	3MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	2052(H)*1536(V)
Max. Image Resolution	No
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	2.8-12mm
Lens Mount	φ14
Adjustment Range	Pan: 0° - 360°; Tilt: 0° - 75°; Rotate: 0° - 360°
Day & Night	IR cut filter with auto switch
Wide Dynamic Range	No
Synchronization	Internal Synchronization
Video Frame Rate	No
HD Video Output	No
Video Output	No
S/N Ratio	12 VDC
Scene	No
Camera ID	No
AGC	Support
D/N Mode	Color/BW/SMART
Auto White Balance	Auto/MWB
Private Mask	No
Motion Detection	No
BLC	Support
Anti-Flicker	No
Language	English/Chinese
Function	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
Operating Conditions	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Weather Proof	IP66
IR Range	Up to 40m
Dimension	φ110mm×93.2mm (φ4.33"×3.67")
Weight	Approx. 350g (0.77lb)
Communication	No