

Connectivity	Wireless
Image Sensor	1/3" progressive scan CMOS
Signal System	No
Min. Illumination	0.01Lux @(F1.2,AGC ON), 0 Lux with IR ; 0.028Lux @(F2.0,AGC ON), 0 Lux with IR
Shutter Time	1/3 s to 1/100,000 s
Lens	2.8mm
Lens Mount	M12
Adjustment Range	No
Day & Night	ICR
Wide Dynamic Range	Digital WDR
Digital Noise Reduction	3D DNR
Video Compression	H.264 / MJPEG
Bit Rate	32Kbps~8Mbps
Dual Stream	No
Max. Image Resolution	2MP
Frame Rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
BLC	Yes, zone optional
ROI	Support
Network Storage	Local storage: Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB. NAS (Support NFS,SMB/CIFS)
Alarm Trigger	Intrusion detection, Line crossing detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Protocols	802.11b: CCK, QPSK, BPSK ; 802.11g / n: OFDM
Security	64 / 128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK, WPS