

IP video input	16- ch Up to 12MP resolution
Two-way audio	1-ch, RCA(2.0 Vp-p,1kΩ)
Incoming bandwidth	160 Mbps
Outgoing bandwidth	256 Mbps
Remote connection	128
Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF
HDMI output resolution	4K (3840 x 2160)/60Hz, 4K (3820 x 2160)/30Hz, 1920 x 1080p/60Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
VGA output resolution	1920 x 1080p/60Hz, 1280 x 1024/60Hz,1280 x 720/60Hz, 1024 x 768/60Hz
Audio output	1-ch,RCA(Linear, 1KΩ)
Decoding format	H.265/H.264/MPEG4
Live view/Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF
Synchronous playback	16-ch
Capability	4-ch @ 4K, or 16-ch @ 1080p
SATA	4 SATA interfaces for 4HDDs
eSATA(optional)	1 eSATA interface
Capacity	Up to 6TB capacity for each HDD
Network interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Serial interface	1 RS-485 (half-duplex), 1 RS-232
USB interface	Front panel: 2 X USB 2.0; Rear panel: 1 x USB 3.0
Alarm in/out	16-Apr
Interface	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
Power	<=200W
Supported standard	IEEE 802.3 af/at
Power supply	100 to 240VAC
Consumption(without hard disk)	<=20W (without enabling PoE)
Working Temperature	-10° t0 +55°C(14° to 131°F)
Working humidity	10 to 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions(W x D xH)	445 x 390 x 70mm (17.5" x 15.3" x 2.8')
Weight(without hard disk)	<=5Kg(11lb)