

| | |
|---------------------------------------|---|
| IP video input | 32- ch Up to 12MP resolution |
| Two-way audio | 1-ch, RCA(2.0 Vp-p,1kΩ) |
| Incoming bandwidth | N/A |
| Outgoing bandwidth | 256 Mbps |
| Remote connection | 128 |
| Recording resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF |
| HDMI output resolution | 4K (3840 x 2160)/60Hz, 4K (3820 x 2160)/30Hz, 1920 x 1080p/60Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz |
| VGA output resolution | 1920 x 1080p/60Hz, 1280 x 1024/60Hz,1280 x 720/60Hz, 1024 x 768/60Hz |
| Audio output | 1-ch,RCA(Linear, 1KΩ) |
| Decoding format | H.265/H.264/MPEG4 |
| Live view/Playback resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF |
| Synchronous playback | 16-ch |
| Capability | 4-ch @ 4K, or 16-ch @ 1080p |
| SATA | 4 SATA interfaces for 4HDDs |
| eSATA(optional) | 1 eSATA interface |
| Capacity | Up to 6TB capacity for each HDD |
| Network interface | 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface |
| Serial interface | 1 RS-485 (half-duplex), 1 RS-232 |
| USB interface | Front panel: 2 X USB 2.0; Rear panel: 1 x USB 3.0 |
| Alarm in/out | 16-Apr |
| Interface | N/A |
| Power | <=80 W |
| Supported standard | N/A |
| Power supply | 100 to 240VAC |
| Consumption(without hard disk) | <=20W |
| Working Temperature | -10° t0 +55°C(14° to 131°F) |
| Working humidity | 10 to 90% |
| Chassis | 19-inch rack-mounted 1.5U chassis |
| Dimensions(W x D xH) | 445 x 390 x 70mm (17.5" x 15.3" x 2.8') |
| Weight(without hard disk) | <=5Kg(11lb) |