

IP video input	64-ch up to 12MP resolution
Two-way audio	1-ch, RCA(2.0 Vp-p,1kΩ)
Incoming bandwidth	320 Mbps, or 200 Mbps (when RAID is enabled)
Outgoing bandwidth	256 Mbps, or 200 Mbps(when RAID is enabled)
Remote connection	128
Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
VGA2/HDMI 2 output resolution	1920x1080p/60Hz, 1280x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
Audio output	2-ch, RCA(2.0Vp-p, 1KΩ)
Decoding format	H.265/H.264/MPEG4
Live view/Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	16-ch
Capability	4-ch @ 4K, or 16-ch @ 1080p
SATA	8 SATA interfaces for 8HDDs
eSATA(optional)	1 eSATA interface
Capacity	Up to 6TB capacity for each HDD
Array Type	RAID0, RAID1, RAID5, RAID10
Number of Array	4
Network interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Serial interface	RS-232; RS-485(reserved); Keyboard;
USB interface	Front panel: 2 X USB 2.0; Rear panel: 1 x USB 3.0
Alarm in/out	16-Apr
Power	200W
Power supply	100 to 240VAC, 50 to 60Hz
Consumption(without hard disk)	<=30W
Working Temperature	-10° t0 +55°C(14° to 131°F)
Working humidity	10 to 90%
Chassis	19-inch rack-mounted 2U chassis
Dimensions(W x D xH)	445 x 470 x 90mm (17.5" x 18.5" x 3.5")
Weight(without hard disk)	<=10kg (22lb)