

<b>Channels</b>	16CH
<b>IP Video Input</b>	None
<b>Two-way Audio</b>	1-ch RCA(2.0Vp-p, 1k $\Omega$ )
<b>VGA Output</b>	1-ch, resolution: 1920×1080P/60Hz,1600×1200/60Hz,1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
<b>CVBS Output</b>	N/A
<b>HDMI Output</b>	1-ch, resolution: 1920 × 1080P /60Hz, 1920 × 1080P /50Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
<b>Recording Resolution</b>	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
<b>Audio Output</b>	1-ch RCA(Linear, 1k $\Omega$ )
<b>Playback Resolution</b>	5MP /3MP / 1080P / UXGA / 720P / 4CIF / VGA / DCIF / 2CIF / CIF / QCIF
<b>Synchronous Playback</b>	8-ch
<b>Interface Type</b>	2 SATA Interfaces
<b>Capacity</b>	Up to 4TB capacity for each disk
<b>e-SATA Interface</b>	N/A
<b>Network Interface</b>	1 RJ45 10M/100M/1000M adaptive Ethernet Interface, 4 independent 100Mbps PoE Ethernet interfaces
<b>PoE</b>	8-Port PoE
<b>USB Interface</b>	2 USB 2.0 Interfaces
<b>Serial Interface</b>	1 RS-485 interface (Reserved)
<b>Alarm Input</b>	N/A
<b>Alarm Output</b>	N/A
<b>Power Supply</b>	100~240VAC, 47~63Hz, 3A
<b>Consumption</b>	≤ 15 W (without hard disk)
<b>Working Temperature</b>	-10 °C ~ +55 °C
<b>Working Humidity</b>	10%~90%
<b>Chassis</b>	19-inch rack-mounted 1U chassis
<b>Dimensions</b>	445 × 290 × 45mm (W x D x H)
<b>Weight</b>	≤ 2 Kg (without hard disk)