

<b>Model</b>		<b>YC-W964AHBB85NA</b>
<b>Camera</b>		
Image Sensor		1/3" OV4689 CMOS
Effective Pixels		2688(H)×1520 (V)
Electronic Shutter		AUTO, 1/25s ~ 1/100000s
Min. Illumination		0.1Lux@F1.2(AGC ON), 0Lux IR on
Day/Night		Auto/Color/(B/W)/Timing
WDR		Digital WDR
White Balance		Auto
Other		rror, Flip
<b>Encode</b>		
Embedded Solution		Hi3516D
Video Standard		H.265/H.264
Video Resolution		@4MP(2592x1520),30fps@3MP/1080P/720P
		Sub stream: VGA(640x480)/360P/QVGA@25fps
Video Bitrates		512Kbps - 6Mbps, VBR/CBR
Audio Standard		G.711-u
<b>IR Led</b>		
IR Led		5pcs Array IR LEDs
IR Distance		15-20m
<b>Lens</b>		
Focal length		Fixed or VF lens
Lens		3.6/6mm
<b>Optional Function</b>		
POE, Audio, Alarm In/Out, SD card, etc.		
<b>Network Services</b>		
Protocol		RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
P2P		Yes
Web		IE , firefox, etc.
Media		CMS, Android, IOS
ONVIF		2.4 compatible
<b>General</b>		
Network Port		1-RJ45, 100Mbps, POE optional
Power Supply		12 VDC ± 10%
Power Consumption		< 5 W
Operating Temp.		-30°C-(+60)°C, 10%-90%RH
Dimension		φ94*80mm
Weight		0.32KG