

Audio Input	4-ch
Video Compression	H.264,H.264+
Analog and HD-TVI video input	4-ch,BNC interface (1.0Vp-p, 75 Ω)connection
Supported camera types	3MP,720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
Video Input Interface	BNC (1.0 Vp-p, 75Ω)
Audio Compression	G.711u
Audio Input Interface	4-ch, RCA (2.0 Vp-p, 1 KΩ)
Two-way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using audio input)
CVBS Output	1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480
HDMI/VGA Output	1920 × 1080 / 60 Hz,1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Frame Rate	Main stream:25fps(p)/30fps(N) Sub-stream:WD1/4CIF@12fps(non-real-time);CIF/QVGA/QCIF(real-time)
Video Bit Rate	32 Kbps-10 Mbps
Stream Type	Video/Video&Audio
Two-way Audio	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Audio Output	1-ch RCA(Linear, 1kΩ)
Audio Bit Rate	64kbps
Dual Stream	Support
Playback Resolution	3MP/1080P/720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Synchronous Playback	4-ch
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, Hik-connect Cloud P2P,DNS, DDNS, NTP, SADP,NFS, iSCSI, UPnP™, HTTPS,ONVIF
Interface Type	1 SATA Interface
Capacity	Up to 6 TB capacity for each disk
Network Interface	1; 10M / 100M self-adaptive Ethernet interface
USB Interface	2 USB 2.0 Interfaces
Serial Interface	1; standard RS-485 serial interface, half-duplex
Alarm Input	4-ch
Alarm Output	1-ch
Power Supply	12V DC
Consumption	≤ 15W(without hard disks)
Working Temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)
Working Humidity	10% ~ 90%
Chassis	Standard 1U chassis

Dimensions	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
Weight	≤1.5 kg(3.3lb)